

# mini aqua®

PART NO. FP2406

GB

## DESCRIPTION

Using the proven functionality of our other mini pumps, the Mini Aqua® is incredibly slim in size. It is designed to give the installation flexibility where the latest generation of A/C units are becoming even smaller.


The Aspen Mini Aqua® pump is designed to be installed:

- Within wall mounted evaporators
- In plastic conduit

## IN THE BOX

- 1 x Mini Aqua® pump
- 1 x Anti Siphoning Device
- 1 x Assembled reservoir including filter, float and lid
- 1 x 150mm Vinyl breather tube 6mm ID
- 1 x 1.5m Suction tube 6mm ID
- 1 x 220mm Blue Inlet hose 14mm ID
- 1 x Drain tray connector
- 2 x Velcro strips
- 2 x Cable ties 140 x 3.6mm
- 4 x Cable ties 300 x 3.6mm

## SPECIFICATIONS

- Pump rating: 230V AC, 16W
- 1PH 50 Hz
- 3A volt-free alarm wires, N.C. contacts rated @ 5A inductive at 230V
- Hall effect semi conductor level sensors, with high level safety
- Maximum water temperature: 40°C
- Continuously rated
- Class II appliance 
- Fully potted
- Thermally protected
- 28mm (h) x 165mm (w) x 28mm (d)
- Weight: 0.18kg

## PERFORMANCE

- Water flow rate: 12L/h at zero head
- Maximum recommended head: 10m
- 21dB(A) @ 1m

